

Clarke®

Clarke®

Wet/Dry Tank Vacuums and Air Vacuums



Wet/Dry Tank and Air Vacuums Offer Durability, Dependability

Clarke's wet/dry vacuums offer stainless steel tanks complete with tool kits usually found only with more expensive models. You can rely on a stainless steel tank vacuum for durability and dependability – just look at these quality features:

- Tough polyethylene heads housing with peripheral discharge motor
- Clamps lock downward to prevent spills if vacuum accidentally overturns
- Rugged polyethylene flanged hose locks into place to eliminate accidental disconnection
- Built-in cable wrap for storage
- Built-in handle for easy transporting
- Large casters and stable base to easily maneuver vacuum without tipping



STV 10 gallon tank vacuum

Clarke manufactures wet/dry tank vacuums in 20-gallon, 15-gallon and 10-gallon sizes. All three sizes, even the smaller 10-gallon, are equipped with a tool kit consisting of a two-piece wand as well as squeegee, bristle, crevice, upholstery and extension tools.

STV 15 & 20 gallon tank vacuum

The 15-gallon stainless steel tank vacuum tilts back on its wheels for easy emptying. An optional front squeegee, available on both the 15-gallon and 20-gallon size vacuums, works in either forward or backward direction for labor-saving clean up of wide areas.

STV 20D gallon tank vacuum

The 20-gallon stainless steel tank vacuum features two 1-hp motors, giving it the power to pick up twice as much cubic feet per minute as the two smaller size vacuums.



DWD Air Vacuum

Clarke's air vacuum will fit any standard 55-gallon drum to create a heavy-duty vacuum that can siphon as much as two gallons per second and provide a water lift of 218 inches. Operating on a simple aerodynamic principle, the DWD air vacuum is virtually maintenance-free without any moving parts.



Air pressure passes through twin jet venturi to create a powerful vacuum. Despite its high air pressure, the noise level remains less than 79 decibels – lower than OSHA requirements. Equipped with a removable filter, the DWD air vacuum can handle wet or dry pickup, including sludge, sand, metal chips or more – an excellent alternative to traditional tank vacuums.

Summit Tank Vacuums



Summit 16SQ Tank Vacuums

The Summit 16-gallon tank vacuum combines durability and dependability features for outstanding performance and hours of uninterrupted cleaning. The rugged Polydur tank is guaranteed to last in the toughest environment.

A 10-inch wheel transport base makes it easy to maneuver, and a large drain hose quickly empties the tank.

Finally, a foot-activated squeegee eliminates the mess and extra work involved with a wand and squeegee tool. This labor-saving floor squeegee works in both forward and reverse to pick up large spills in wide areas.






Summit Pumper Tank Vacuums

When you must clean areas where a floor drain is not available, you need to dispose of the dirty solution where you want it. The Summit pumper tank vacuum is powerful enough to pick up and discard solutions into drums, janitorial sinks or commodes up to 50 inches high.

You may also need a vacuum that can move through areas where a 55-gallon drum cannot – another ideal situation for the Summit pumper tank vacuum. Clarke provides an eight-year warranty on the tank and a three-year warranty on the motor housing and cover assembly – you just can't beat the durability of this vacuum.




Wet/Dry Tank Vacuums and Air Vacuums

Clarke®



SPECIFICATIONS

Model	STV-20D	STV-20	STV-15	STV-10
Motor (115 volt, 230 volt)	two 1-hp		1.5 hp	
CFM and water lift	200, 71 in.		100, 87 in.	
Filter type(dry)	polyester			
Hose size	1½ in. (3.8 cm) x 8 ft. (244 cm)			
Tool kits	standard			
Tank size	20 gal.		15 gal.	10 gal.
Wheel size	two 10 in. rear		two 8 in. rear	four 1½ in. front
Caster size	two 3 in. front		two 3 in. front	and rear
Power cable	27.5 ft. (8.4 m)			28 ft. (8.6 m)
Applications	wet and dry			
Optional squeegee	yes		yes	no
Machine weight	57 lbs. (26 kg)	50.5 lbs. (23 kg)	46 lbs. (20.9 kg)	22 lbs. (9.9 kg)
Shipping weight	69 lbs. (31 kg)	62 lbs. (28 kg)	52 lbs. (23.5 kg)	27 lbs. (12.2 kg)



SPECIFICATIONS

Model	DWD Air	Summit 16SQ	Summit Pumper
Motor	Air powered 60 psi/70 cfm	1 hp. bypass two-stage tangential discharge	1 hp. bypass two-stage tangential discharge
Air movement	230	94 cfm (44,363 cm ² /S)	94 cfm (44,363 cm ² /S)
Water lift	218 in. (553.7 cm)	84 in. (213.4 cm)	84 in. (213.4 cm)
Filter area	3.95 sq. ft. self cleaning	4 sq. ft.	N/A
Hose adapter	2 in. (5.1 cm)	1.5 in. (3.8 cm)	1.5 in. (3.8 cm)
Tank size	55 gal. drum available	16 gal. (60.6 l.)	16 gal. (60.6 l.)
Tools	2 in. tools available		1½ in. hose, tools optional
Capacity		16 gal. (60.6 l.)	16 gal. (60.6 l.)
Wheels	N/A	two 10 in. (25.4 cm) transport one 4 in. (10.2 cm) caster	two 10 in. (25.4 cm) transport one 4 in. (10.2 cm) caster
Power cable	none required	50 ft. (15.2 m) 3 conductor	50 ft. (15.2 m) 3 conductor
Dimensions	45 in. height w/drum & base 24 in. diameter	38 in. x 35 in. x 24 in. (96.5 cm x 88.9 cm x 61.0 cm)	38 in. x 35 in. x 24 in. (96.5 cm x 88.9 cm x 61.0 cm)
Weight	43 lbs. (19.5 kg)	65 lbs. (29.5 kg)	63 lbs. (28.6 kg)
Shipping weight	51 lbs. (23.1 kg)	86 lbs. (39.0 kg)	86 lbs. (39 kg)
Warranty	1 year motor	8 year tank, 3 year powerhead	8 year tank, 3 year powerhead

Clarke®

2100 Hwy. 265
Springdale, AR 72764
www.clarkeus.com

DISTRIBUTED BY:

CleanCraft Products, Inc.
800-525-3261
www.cleancraft.com

